



IPvlan

Eric Dumazet (edumazet@google.com)

Mahesh Bandewar (maheshb@google.com)

IPvlan (instead of MACvlan) : Why?

- Switches may apply policies to disable CAM-table overflow essentially allowing a mac-address per incoming frame per port
- Excessive use of mac-addresses per NIC on host may put the host in promiscuous mode.
 - Might have impact if the connected switch starts throwing all multicast traffic as well.
- Other alternatives are not really well performing
 - NAT
 - Forwarding

IPvlan: Development Challenges, Choices

- Integrate changes into macvlan itself
 - Proved difficult without any compromises
- Broadcast / Multicast tweaks
 - Turn-off broadcast if IPv4 is not used.
 - Use multicast filter in decision making while forwarding to slave
- Communication with Master (mostly in *init_ns*)
 - macvlan solves this with hairpin-mode support from connected switch
 - IPvlan can't do this (same L2 address)!

IPvlan: Development Challenges, Choices (continue...)

- To communicate with host the setup need to put host on the same IPvlan bridge as rest of the slaves.
- Alternatively there are patches to the stack to inject routes in the master's namespace to redirect packets. These were viewed as too intrusive.




Fig: Current Host-setup









Fig: Alternative Host-setup

IPvlan: Use Cases

- IPvlan in L2 mode [slave(s) assigned to namespace(s)]
 - Setup is similar to several hosts connected to an external switch.
 - This is very similar to macvlan bridge mode.
 - Each slave can operate on it's own [IP, routing etc.]
 - Suited in trusted environment.
- IPvlan in L3 mode [slave(s) assigned to namespace(s)]
 - All slaves receive only unicast. Master handles rest.
 - Each slave relies on the routing from the masters' namespace.
 - Tinkering with IP inside namespace may lose connectivity.
 - Suited in non-trusted environment.

IPvlan: Performance comparison



IPvlan Setup

IPvlan: Future Enhancements

- Defer multicast / broadcast traffic processing.
 - Deferring will boost unicast throughput and improve latencies
 - Doesn't need to process these in fast-path.
- ARP filters.
 - Applicable to IPv4 only
 - Probe into the ARP and forward only when slave may have interest.
 - Will save on packet duplication when slaves are many.
- Tap type slave device interface for Kvm/Qemu.
 - Similar to macvtap

IPvlan: Future Enhancements (continue...)

- Offload XMIT to hardware if NIC supports it.
 - Similar to few current Intel NICs for macvlan.
 - Can't use just L2 and logic needs to include L3 (possibly more?)
- Enhanced L3 mode to enable communication with master.
 - L3 mode does not deal with broadcast and multicast.
 - If master has to communicate with other slave, then should use same bridge.
 - Nominate one of the slaves to receive broadcast / multicast
- Userspace support
 - Docker
 - CRIU

IPvlan: Questions? Comments?

