


Integrating Power over Ethernet and Power over Dataline support to the Linux kernel

Oleksij Rempel - ore@pengutronix.de




What is Power over Ethernet?

- PSE – power source equipment
- PD – powered device
- Power delivered over two pairs. One pair +, other pair -




What is PoE4?

- Same as PoE but more power
- For power delivery are used all 4 pairs



What is PoDL?

- Power over Data Line
- Same as PoE, except power is delivered over one twisted pair
- PoDL needs different filter implementation compared to PoE* variants



Detection

- Optional
- PSE provides a constant current on the line and measures the voltage drop if PD is connected



Classification

- Optional functionality
- PoE and PoDL have different way for classification.
- PoDL is using SCCP – simple, digital, one-wire communication serial classification protocol.
- PoE uses a constant voltage from the PSE and a current sink on the PD to signal the power class



Current kernel implementation

- Provides per network port ethtool interface
- Currently we can:
 - control admin state of PSE per port independent of link admin state
 - Read admin state and status of PSE



WIP ethtool implementation

- `$ ip l`
- ...
- `5: t111@eth0: <BROADCAST,MULTICAST> ..`
- ...
- `$ ethtool --show-pse t111`
- PSE attributes for t111:
- PoDL PSE Admin State: disabled
- PoDL PSE Power Detection Status: disabled
-
- `$ ethtool --set-pse t111 podl-pse-admin-control enable`
- `$ ethtool --show-pse t111`
- PSE attributes for t111:
- PoDL PSE Admin State: enabled
- PoDL PSE Power Detection Status: delivering power



Thank you!

Questions?

